Electrotherapy method utilizing patient dependent electrical parameters

Publication number: JP9500309 (T)
Publication date: 1997-01-14
Inventor(s):
Applicant(s):
Classification:
- **international:** ***A61N1/39***; **A61N1/39**; (IPC1-7): A61N1/39
- **European:** A61N1/39C4
Application number: JP19940506957T 19940719
Priority number(s): WO1994US08134 19940719; US19930103837 19930806, US19940227553 19940414

Also published as:
US5749904 (A)
US5603927 (A)
WO9505215 (A2)
WO9505215 (A3)
NO960470 (A)
more >>

Abstract not available for JP 9500309 (T)
Abstract of corresponding document: **US 5749904 (A)**

The invention provides a method for delivering electrotherapy to a patient through electrodes connected to a plurality of capacitors, including the steps of discharging at least one of the capacitors across the electrodes to deliver electrical energy to the patient, monitoring a patient-dependent electrical parameter (such as voltage, current or charge) during the discharging step, and adjusting energy delivered to the patient based on a value of the electrical parameter. The adjusting step may include selecting a serial or parallel arrangement for the capacitors based on a value of the electrical parameter. In another embodiment, the invention provides a method for delivering electrotherapy to a patient through electrodes connectable to a plurality of capacitors including the steps of discharging at least one of the capacitors across the electrodes to deliver electrical energy to the patient in a waveform having at least a first phase and a second phase, monitoring a patient-dependent electrical parameter (such as voltage, current or charge) during the discharging step, and modifying second phase initial voltage based on a value of the electrical parameter. The adjusting step may include selecting a serial or a parallel arrangement for the capacitors based on a value of the electrical parameter.



Data supplied from the *espacenet* database — Worldwide